



Tweeters



Driver specifications, tweeters

Latest update: October 18, 2020

Photo no. (opposite page)	Driver Part no.	Nom. size	Nom. imp.	Freq. range	Sensitivity	VC. diam.	X _{max}	S _d	F _s	M _{ms}	BxI	Q _{ms}	Q _{es}	Q _{ts}	V _{as}	R _{DC}
		[mm]	[ohm]	[kHz]	[dB@2.83V/1m]	[mm]	[mm]	[cm ²]	[Hz]	[g]	[N/A]	[-]	[-]	[-]	[mlit.]	[ohm]
T1	TW013WA01	13	4	5-50	87	13	±0.3	2.1	1,300	0.12	0.71	1.7	5.3	1.29	0.81	2.9
T2	TW022WA02	22	4	2.5-30	88.5	22	±0.45	6.1	1,150	0.28	1.33	1.5	4.1	1.11	3.6	3.6
T3	TW022WA04	22	4	2-30	89.5	22	±0.45	6.1	825	0.26	1.6	1.4	1.9	0.80	7.6	3.6
T4	TW022WA05	22	4	2.5-25	91.5	22	±0.35	6.1	750	0.28	1.9	5.3	1.36	1.08	8.5	3.7
T4	TW022WA06	22	4	2-25	90.5	22	±0.35	6.1	750	0.30	1.9	2.5	1.45	0.92	7.9	3.7
T10	TW022WA09	22	4	2-30	92	22	±0.35	6.1	700	0.27	1.8	1.3	1.2	0.62	10	3.1
T10	TW022WA10	22	8	2-30	89.5	22	±0.35	6.1	730	0.25	2.2	1.2	1.4	0.66	10	6.0
T5	TW030WA01	30	4	2-25	94	30	±0.65	11.5	1,050	0.42	2.3	4.8	1.78	1.30	10.3	3.4
T5	TW030WA02	30	4	2-25	94	30	±0.65	11.5	1,100	0.45	2.5	1.2	1.69	0.70	8.7	3.4
T6	TW030WA05	30	4	1.5-25	91.5	30	±0.4	11.5	450	0.40	2.0	1.5	0.96	0.59	59	3.4
T6	TW030WA06	30	4	1.5-25	91	30	±0.4	11.5	450	0.42	2.0	1.2	1.01	0.55	56	3.4
T6	TW030WA07	30	8	1.5-25	89	30	±0.4	11.5	470	0.37	2.4	1.6	1.19	0.68	59	6.3
T6	TW030WA08	30	8	1.5-25	88.5	30	±0.4	11.5	470	0.39	2.4	1.3	1.25	0.64	56	6.3
T7	TW030WA09	30	4	2-27	92.5	30	±0.4	11.5	725	0.45	2.0	8.1	1.74	1.43	20	3.4
T7	TW030WA10	30	8	2-27	90	30	±0.4	11.5	750	0.42	2.4	7.8	2.17	1.70	20	6.3
T8	TW030WA11	30	4	1.5-25	93.5	30	±0.4	11.5	410	0.43	1.7	1.9	1.34	0.79	66	3.5
T8	TW030WA12	30	8	1.5-25	91	30	±0.4	11.5	425	0.40	2.0	1.9	1.74	0.90	66	6.5
T9	TW030WA13	30	4	2-30	93.5	30	±0.4	11.5	690	0.43	1.95	2.5	1.62	1.01	23	3.5
T9	TW030WA14	30	8	2-30	90.5	30	±0.4	11.5	715	0.40	2.25	2.4	2.31	1.17	23	6.5

All specifications are measured at 25 °C (77 °F) and are before burn-in.